

### Automation for sliding pedestrian doors

#### ▶ Valor Developed today with the future in mind

The new range of Valor automations offers the latest industry innovations with its last generation electromechanical components and innovative control panel.

Practical and safe, the automation is sure to enhance the look of your entrance and, when fitted in air conditioned areas, to optimise energy consumption.

Available in different models

#### ▶ Distinctive Features

- ▶ Wide range of models
- ▶ Built-in the head display (optional)
- ▶ Built-in safety sensors (optional)
- ▶ Self adjusting automatic closing time when pedestrian traffic is heavy
- ▶ Self adjusting access opening when pedestrian traffic is heavy
- ▶ Advanced electronics
- ▶ Analogue programming and control display
- ▶ Quiet operation thanks to the vibration proof guide
- ▶ Self supporting facility on all models with heavy casing
- ▶ Wide range of dedicated accessories

#### ▶ Technical Specifications

	VALOR
Duty class	5 - very heavy and/or 6 - continuous - 3 millions of operations
Travel control system	Encoder
Mains power supply	230 VAC / 50-60 Hz
Input	1 A
Opening speed	0.8 m/s (1 wing) 1.6 m/s (2 wings)
Closing speed	0.8 m/s (1 wing) 1.6 m/s (2 wings)
Intermittent operation	S3 = 100%
Maximum capacity	120 kg (1 wing) 240 kg (2 wings)
Capacity with reinforced wheels (VALOR B and N)	150 kg (1 wing) 300 kg (2 wings)
Temperature	- 20° C / + 55° C (-10°C / +50°C with batteries)
Protection rating	IP 20
Product dimensions	175 x 145 x L
Control panel	EL20 (built-in)

